

MAXIMUS RE

The most compact thermoformer available!




PACKAGING MADE SIMPLE, THE COMPACT SOLUTION FOR YOUR GROWING BUSINESS!

The Maximus RE is the ideal solution for small production environments with limited space. Thanks to its compact design and integrated control cabinet, it enables a space-saving setup and maximum efficiency. The intuitive 10-inch HMI Panel ensures precise process monitoring, while the standard film width of 420 mm and 6 different stroke lengths support versatile applications. Its well-thought-out design allows for dual-sided use at the loading area, further enhancing user convenience.

- \cdot 2.200 mm length x 750 mm width, < 1,7 m² footprint
- 6 different stroke lengths allow different and versatile applications
- · Integrated electrical cabinet for space-saving footprint
- · Loading area usable from both sides
- · 10-inch HMI panel, swiveling (IP67)
- · Emergency stop switch on both sides of the machine
- · Short delivery times thanks to efficient pre-assembly







MAXIMUS RE

Technical Info | Available Options

• Film width: 420 mm

• Available stroke lengths: 200 / 230 / 260 / 280 / 300 / 320 mm

• Maximum draw depth: 90 mm

• Format: 2.1 (always included)

• Packaging types: Sealing, Vacuum, MAP (flexible film)

• Output: max. 6 cycles/min.

• **Electrical voltage:** 3 x 230 V N/PE | 3 x 400 V N/PE | 50/60 Hz | IP65

· Compressed air: min. 6 bar

Vacuum pump: 063 cbm/h (internal)






Available options:

Gas flush | 100 cbm/h Vacuum pump Machine on casters | Change format Photo cell control for registered top web Perimeter sealing plates | Cooling unit

Available devider sets



EASY TO CONFIGURE | FULL-FEATURED | COMPACT

